

Modular Cooking Range Line 700XP Two Wells Gas Fryer Top 7 liter

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		
AIA #		



371067 (E7FRGH2B00)

7+7-It gas Fryer Top with 2 "V" shape wells (external Burners) and 2 baskets

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. Two high efficiency 7 kW burners in stainless steel. Suitable for natural gas or LPG. Deep drawn V-shaped well. Oil drains through a tap on the front. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Deep drawn V-Shaped wells.
- Interior of wells with rounded corners for ease of cleaning.
- Two high efficiency 7 kW burners in stainless steel with flame failure device attached to the outside of the wells.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Flame failure device on each burner.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap positioned on the front the wells.
- All major compartments located in front of unit for ease of maintenance.
- · Piezo spark ignition for added safety.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPx4 water protection.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.
- Suitable for countertop installation.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Sustainability



This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

Included Accessories

 2 of Basket for 7lt top and free standing fryers

PNC 921608

Optional Accessories

installation, 1600mm

-		
 Junction sealing kit 	PNC 206086	
 Draught diverter, 150 mm diameter 	PNC 206132	
• Matching ring for flue condenser, 150 mm diameter	PNC 206133	
 Support for bridge type installation, 800mm 	PNC 206137	
 Support for bridge type installation, 1000mm 	PNC 206138	
 Support for bridge type installation, 1200mm 	PNC 206139	
 Support for bridge type installation, 1400mm 	PNC 206140	
 Support for bridge type 	PNC 206141	

APPROVAL:





Modular Cooking Range Line 700XP Two Wells Gas Fryer Top 7 liter

PNC 206246	
PNC 206304	
PNC 206307	
PNC 206308	
PNC 206400	
PNC 206467	
PNC 216277	
PNC 921608	
PNC 927225	
PNC 960638	
	PNC 206304 PNC 206307 PNC 206308 PNC 206400 PNC 206467 PNC 216277 PNC 921608





Modular Cooking Range Line 700XP Two Wells Gas Fryer Top 7

Front 13 1/8 " G 333 റീ റീ 2 1/16 52 mm 0 7/16 30 5/8 " 0 7/16 " 11 mm 778 mm 11 mm Side 28 3/4 " 730 mm 2/8 82 9 . S 55 10 7/16 E 2/8 265 1 3/8 250 35 6 E EQ25 2 3/8 " 3 " 60 mm 76 mm G 4 " 102 mm 5 13/16 " 17 11/16 " 4 9/16 " 148 mm 116 mm 450 mm EQ Equipotential screw Gas connection Top 31 1/2 " 800 mm 3/16 E 730 792 82 31

Gas

Gas Power:

371067 (E7FRGH2B00) 14 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG;Natural Gas

Working pressure, mBar (min/Max): 0/0 1/2" Gas Inlet:

Key Information:

Usable well dimensions

(width): 240 mm Usable well dimensions

235 mm (height):

Usable well dimensions (depth): 380 mm

Well capacity: 5.5 It MIN; 7 It MAX

Thermostat Range: 105 °C MIN; 185 °C MAX 47 kg Net weight: Shipping weight: 54 kg

Shipping height: 540 mm Shipping width: 820 mm Shipping depth: 860 mm Shipping volume: 0.38 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

Certification group: N7FG



Modular Cooking Range Line 700XP Two Wells Gas Fryer Top 7 liter