

Modular Cooking Range Line 900XP 400mm Electric Fry Top, Smooth Brushed Chrome Plate

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



391357 (E9IINDAOMCA) Half module electric Fry Top with smooth brushed chrome cooking Plate, horizontal, thermostatic control, scraper and sTopper included

391398 (E9IINIAOMCA) Half module electric Fry Top with smooth brushed chrome cooking Plate, horizontal, 230V, thermostatic control, scraper and sTopper included

Short Form Specification

Item No.

Smooth cooking surface in brushed chrome. Temperature range from 120°C to 280°C. To be installed on open base installations, bridging supports or cantilever systems. Removable drawer below the cooking surface for the collection of grease and fat. Body and work top of unit entirely in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1 liter collector placed under the cooking surface.
- Electric elements in incoloy positioned under the cooking plate.
- Safety thermostat and thermostatic control.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwashersafe.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Temperature range from 120° up to 280°C.
- Rough brushed chrome surface is highly resistant to scratches and facilitates cleaning operations at the end of the day.
- Scraper for smooth plate included as standard.
- Suitable for countertop installation.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Cooking surface 15mm thick brushed chrome for optimum grilling results and ease of use.
- Cooking surface completely smooth.

Included Accessories

- 1 of Scraper for smooth plate fry PNC 164255 tops
- 1 of Stopper for 900 fry top with PNC 206296 horizontal plate

Optional Accessories

installation, 400mm

• Scraper for smooth plate fry tops	PNC 164255	
 Junction sealing kit 	PNC 206086	
 Support for bridge type installation, 800mm 	PNC 206137	
 Support for bridge type installation, 1000mm 	PNC 206138	
 Support for bridge type installation, 1200mm 	PNC 206139	
 Support for bridge type installation, 1400mm 	PNC 206140	
 Support for bridge type installation, 1600mm 	PNC 206141	
 Water drain for half module fry tops 	PNC 206153	
Support for bridge type	PNC 206154	

APPROVAL:





Modular Cooking Range Line 900XP 400mm Electric Fry Top, Smooth Brushed Chrome Plate


• Stopper for 900 fry top with horizontal plate	PNC 206296	
Back handrail 800 mm	PNC 206308	
Back handrail 1200 mm	PNC 206309	
 Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module) 	PNC 206346	
• Chimney grid net, 400mm (700XP/900)	PNC 206400	
 Cloche for fry tops 	PNC 206455	
• Side handrail-right/left hand (900XP)	PNC 216044	
• Frontal handrail, 400mm	PNC 216046	
• Frontal handrail, 800mm	PNC 216047	
• Frontal handrail, 1200mm	PNC 216049	
• Frontal handrail, 1600mm	PNC 216050	
 Large handrail - portioning shelf, 400mm 	PNC 216185	
 Large handrail - portioning shelf, 800mm 	PNC 216186	
 2 side covering panels for top appliances 	PNC 216278	






Modular Cooking Range Line 900XP 400mm Electric Fry Top, Smooth Brushed Chrome Plate

Front E 3/16 386 mm 9 0 52 mm E Q 5 15/16 " ΕI 151 mm 5 15/16 " 151 mm 0 7/16 " 0 7/16 14 7/8 11 mm 378 mm 11 mm



FΩ

Equipotential screw



Electric

Supply voltage:

391357 (E9IINDAOMCA) 380-400 V/3 ph/50/60 Hz **391398 (E9IINIAOMCA)** 230 V/3 ph/50/60 Hz

Total Watts: 7.5 kW

Predisposed for:

380-400V 3~ 50/60Hz

391357 (E9IINDAOMCA) 6,7-7,5kW

Key Information:

Cooking surface width: 330 mm
Cooking surface depth: 700 mm
Working Temperature MIN: 120 °C
Working Temperature MAX: 280 °C
External dimensions, Width: 400 mm
External dimensions, Depth: 930 mm
External dimensions, Height: 250 mm
Net weight: 55 kg

Shipping weight:

391357 (E9IINDAOMCA) 56 kg
391398 (E9IINIAOMCA) 65 kg
Shipping height: 540 mm
Shipping width: 460 mm
Shipping depth: 1020 mm
Shipping volume: 0.25 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

