

Modular Cooking Range Line 900XP 800mm Electric Fry Top, Smooth Brushed Chrome Plate

| ITEM # | |
|---------|--|
| MODEL # | |
| NAME # | |
| SIS # | |
| AIA# | |



391400 (E9IINDAOMEA) Full module electric Fry Top with smooth brushed chrome cooking Plate, horizontal, thermostatic control, scraper and sTopper included

391399 (E9IINIAOMEA) Full module electric Fry Top with smooth brushed chrome cooking Plate, horizontal, 230V, thermostatic control, scraper and sTopper included

Short Form Specification

Item No.

Smooth cooking surface in brushed chrome. Temperature range from 120°C to 280°C. To be installed on open base installations, bridging supports or cantilever systems. Removable drawer below the cooking surface for the collection of grease and fat. Body and work top of unit entirely in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1 liter collector placed under the cooking surface.
- Electric elements in incoloy positioned under the cooking plate.
- Safety thermostat and thermostatic control.
- Units have separate controls for each half module of the cooking surface.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwashersafe.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Temperature range from 120° up to 280°C.
- Rough brushed chrome surface is highly resistant to scratches and facilitates cleaning operations at the end of the day.
- Scraper for smooth plate included as standard.
- Suitable for countertop installation.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Cooking surface 15mm thick brushed chrome for optimum grilling results and ease of use.
- Cooking surface completely smooth.

Included Accessories

| • 1 of Scraper for smooth plate fry tops | PNC 164255 |
|--|------------|
| 1 of Stopper for 900 fry top with horizontal plate | PNC 206296 |

| Optional Accessories | |
|--|--------------|
| • Scraper for smooth plate fry tops | PNC 164255 🗖 |
| Junction sealing kit | PNC 206086 🗖 |
| Support for bridge type installation, 800mm | PNC 206137 🗖 |
| Support for bridge type installation, 1000mm | PNC 206138 □ |
| Support for bridge type installation, 1200mm | PNC 206139 🗖 |
| Support for bridge type installation, 1400mm | PNC 206140 🗖 |

APPROVAL:






Modular Cooking Range Line 900XP 800mm Electric Fry Top, Smooth Brushed Chrome Plate

| • Support for bridge type installation, 1600mm | PNC 206141 | |
|---|------------|--|
| Stopper for 900 fry top with horizontal plate | PNC 206296 | |
| • Chimney upstand, 800mm (only for 391400) | PNC 206304 | |
| Back handrail 800 mm | PNC 206308 | |
| Back handrail 1200 mm | PNC 206309 | |
| Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module) | PNC 206346 | |
| Chimney grid net, 400mm (700XP/900) | PNC 206400 | |
| Cloche for fry tops | PNC 206455 | |
| Side handrail-right/left hand (900XP) | PNC 216044 | |
| • Frontal handrail, 800mm | PNC 216047 | |
| • Frontal handrail, 1200mm | PNC 216049 | |
| • Frontal handrail, 1600mm | PNC 216050 | |
| Water drain for full module fry tops | PNC 216153 | |
| Large handrail - portioning shelf, 800mm | PNC 216186 | |
| 2 side covering panels for top appliances | PNC 216278 | |






Modular Cooking Range Line 900XP 800mm Electric Fry Top, Smooth Brushed Chrome Plate



Electrical inlet (power)



Electric

Supply voltage:

391400 (E9IINDAOMEA) 380-400 V/3 ph/50/60 Hz **391399 (E9IINIAOMEA)** 230 V/3 ph/50/60 Hz

Total Watts: 15 kW

Predisposed for:

380-400V 3~ 50/60Hz

391400 (E9IINDAOMEA) 13,5-15kW

Key Information:

Cooking surface width: 730 mm Cooking surface depth: 700 mm Working Temperature MIN: 120 °C **Working Temperature MAX:** 280 °C External dimensions, Width: 800 mm External dimensions, Depth: 930 mm External dimensions, Height: 250 mm Net weight: 105 kg Shipping weight: 391400 (E9IINDAOMEA) 103 kg 391399 (E9IINIAOMEA) 102 kg Shipping height: 391400 (E9IINDAOMEA) 580 mm 391399 (E9IINIAOMEA) 540 mm Shipping width: 391400 (E9IINDAOMEA) 1010 mm 391399 (E9IINIAOMEA) 1020 mm 860 mm Shipping depth: Shipping volume: 391400 (E9IINDAOMEA) 0.5 m³

391399 (E9IINIAOMEA)

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

0.47 m³

