

Double induction cooker

239285

Very clean design suitable for live cooking. Very flat housing with stainless steel frame. Surface of ceramic glass with integrated digital display.

Touch-sensitive controls, power or temperature adjustable in 10 steps. With boost mode which temporarily shifts some power from right hob to the left hob, providing up to 2000 W. The left side hob can output 1800 W, or 2000 W while the boost function is active. The right side hob can output 1700 W, or 1500 W while the boost function is active. Temperature range: 35°-240°C. Suitable for pans with bottom diameter between 120 and 220 mm. Maximum load of the induction cooker: 2x 15 kg.



Specifications

Usage area	: Kitchen
Voltage	: 230
Temp range from [°C]	: 35°C
Temp range to [°C]	: 240°C
Unit temperature	: Celsius
Heating element	: Induction
Protections	: Overheat protection
Electrician needed	: No
Materials	: Stainless steel
Packed per	: 1
Packaging type	: Box
Length (mm)	: 608
Width (mm)	: 370
Height (mm)	: 61
Power (input) (W)	: 3500
Programmable	: No
Measurements	: 608x370x(H)61

Transport specifications

EAN	: 8711369239285
Intrastat code	: 84198180
Gross weight (kg)	: 7.25
Net weight (kg)	: 6.3
Export carton length (mm)	: 680
Export carton width (mm)	: 225
Export carton height (mm)	: 475
Quantity per export carton	: 2
Sales units per pallet	: 30
Plastic packaging (gram)	: 164

HENDI B.V.
 Innovatielaan 6
 6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
 ul. Firmowa 12
 62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
 Ehrling 15
 5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
 Str. 13 decembrie 94A, Hala 14
 Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
 5 Metsovou Str.
 18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
 Via Leonardo da Vinci 4
 39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu