



CA7912DH

CANNAREGIO PROOFER
for VENEXIA COMBI-BAKERY OVENS
12 TRAYS 600x400 - GN 1/1
DIGITAL CONTROL



FUNCTIONAL CHARACTERISTICS

Overlapping oven	SG04*-SM05* SG06*-SM07* SG08*-SG10*-SM12*
Display	DIGITAL
Supply	ELECTRIC
Timer	-
Max proofing temperature (°C)	60°C
Core probe	-
Cooking chamber material	AISI430
Opening door	Double door

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet PA-BIV 6/75
Max tray load	4kg

DIMENSIONS

Size with handle WxDxH (mm)	792 x 893 x 706
Chamber size WxDxH (mm)	702 x 825 x 621
Unit weight (Kg)	48

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	850 x 940 x 832
Unit weight with packaging (Kg)	62
Crate packaging size (optional)	-

ELECTRICAL DATA

Power	2,4kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	10,5A
Power cord req.	3G1,5



WATER CONNECTION REQUIREMENTS

Humidification Water inlet	Male 3/4" GAS
Water drain	-
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA

